- 1. All work shall conform to the requirements of Section 600 of the "Idaho Standards for Public Works Construction" (ISPWC) and the City of Coeur d'Alene Standard Drawings and Specifications. In the case of conflict, City of Coeur d'Alene Standards shall prevail.
- 2. Location and elevation of existing facilities should be confirmed by field measurements and excavation exploration by the contractor, prior to beginning of new work.
- 3. Stormwater Division does not respond to "One-Call" notification. They must be called separately for locates on Storm Drain at (208)769-2235.
- 4. The contractor must secure approval from the City of Coeur d'Alene Streets & Engineering Inspector prior to backfill over Storm Drain mainline.
- 5. The City of Coeur d'Alene Streets & Engineering Inspector shall be notified at least forty-eight (48) hours prior to commencing work on Storm Drains.
- 6. All public storm drain lines shall be CCTV and submitted on DVD in a <u>usable formatted template using "POSM" or another pre-approved equivalent program</u> to the City Streets and Engineering Department for review and approval prior to pavement. Please allow 48 hours for review. <u>Call (208)769-2285</u> for inspection scheduling.
- 7. Manholes and pipes shall be identified using City provided Asset ID numbers. Call (208)769-2285 for Asset ID numbers.
- 8. All manholes, drywells, and catch basins shall be inspected twice by the City of Coeur d'Alene Streets & Engineering Inspector prior to backfill and prior to acceptance of improvements. Call (208)769-2285 for inspection scheduling.

REVISION	APPROVED	DATE	CITY OF COEUR d'ALENE STANDARD DRAWING	APPROVED BY:
			CTODM CVCTEM	Chris Bosley 6/13/18
			STORM $SYSTEM$	CITY ENGINEER, PE 10804 DATE:
			NOTFS	DWG NO.
			NOTES	M-33